



elo USB IO-Link Master

The elo USB IO-Link Master tool is used to operate sensors and actuators with IO-Link interface. The IO-Link devices are described using XML device descriptions and can therefore be monitored and configured quickly and easily. The tool serves to preset, test and demonstrate IO-Link devices. The tool is not intended for day-to-day operation in production systems.

Product characteristics

- Universal IO-Link Master with PC software
- For devices with IODD specification 1.0 and 1.1
- Status LED for IO-Link and SIO mode
- M12 connection for devices

Electrical data

Attribute	350747
Polarity reversal protection	yes
Operating voltage max.	24 V DC
Power supply	5 V / 500 mA (PC USB), 24 V / 80 mA (IO-Link Device aus USB), 24 V / 1 A (IO-Link Device aus Netzgerät)

Properties

Attribute	350747
Suitable for	alle Sensoren mit IO-Link
Accessories supplied	elo USB IO-Link Master, USB A-B Kabel, Netzgerät 24 V DC / 24 W
Function	Konfigurier- und Testgerät für IO-Link

Environmental conditions

Attribute	350747
Operating temperature min.	0 °C
Max. operating temperature	45 °C

Connection

Attribute	350747
Connection type	USB (Mini USB B) Typ 2.0 / Buchse M12