



**Part no.: 50115738**  
**Access Point f. IT**  
**Base station**



Figure can vary

## Contents

- Technical data
- Electrical connection
- Operation and display
- Accessories

Part no.: 50115738 – Access Point f. IT – Base station

## Technical data

### Basic data

Suitable for	IT 1902g series mobile 2D-code readers IT 1911i series mobile 2D-code readers IT 1981i series mobile 2D-code readers
--------------	--

### Electrical data

#### Performance data

Supply voltage $U_B$	4.75 ... 5.25 V , DC
----------------------	----------------------

### Interface

Type	RS 232 USB
------	---------------

### Connection

Number of connections	2 Piece(s)
Bluetooth range	Class 2
Bluetooth version	2.1

#### Connection 1

Type of connection	RJ41
Function	Configuration interface Data interface Voltage supply

#### Connection 2

Type of connection	Bluetooth
Function	Configuration interface Data interface

### Mechanical data

Dimension (W x H x L)	71 mm x 28 mm x 110 mm
Housing material	UL 94-V0

### Operation and display

Type of display	LED
Operational controls	Button(s)
Function of the operational control	Paging

### Environmental data

Ambient temperature, operation	0 ... 50 °C
Ambient temperature, storage	-40 ... 60 °C

### Certifications

Certifications	c UL US
----------------	---------

### Classification


Customs tariff number	85176200
eCl@ss 8.0	27289290
eCl@ss 9.0	27289290
ETIM 5.0	EC002997
ETIM 6.0	EC002997

Part no.: 50115738 – Access Point f. IT – Base station

## Electrical connection

Connection 1	
Type of connection	RJ41
Function	Configuration interface Data interface Voltage supply

Pin	Pin assignment
1	Shield
2	Cable ID
3	GND
4	TxD RS 232 / n.c. USB
5	RxD RS 232 / n.c. USB
6	CTS RS 232 / n.c. USB
7	+5 V DC
8	RTS RS 232 / n.c. USB
9	n.c. RS 232 / Data + USB
10	n.c. RS 232 / Data - USB



Connection 2	
Type of connection	Bluetooth
Function	Configuration interface Data interface


## Operation and display

### LEDs


LED	Display	Meaning
1	Blue, flashing	Establishing a connection
	Blue, continuous light	Operational readiness
	Blue, 1x flashing	Data transmission active

## Accessories


### Connection technology - Connection unit

	Part no.	Designation	Article	Description
	50113397	KB JST-HS-300	Connection cable	Suitable for interface: RS 232 Connection 1: JST ZHR Connection 2: Sub-D, Axial, Male, 9 -pin Shielded: Yes Cable length: 300 mm Sheathing material: PUR

Part no.: 50115738 – Access Point f. IT – Base station

	Part no.	Designation	Article	Description
	50112891	MA 248i Profinet Gateway	Modular connection unit	Supply voltage: 18 ... 30 V Current consumption, max.: 300 mA Interface: PROFINET, RS 232 Connections: 6 Piece(s) Degree of protection: IP 65

Connection technology - Interconnection cables

	Part no.	Designation	Article	Description
	50114517	KB 232-1 IT190x	Interconnection cable	Suitable for interface: RS 232, TTL Connection 1: Sub-D, Axial, Female, 9 -pin Connection 2: RJ41 Connection 3: Connector, Pluggable, Axial, Female, 2 -pin Shielded: Yes Cable length: 3,000 mm Sheathing material: PVC