



Part no.: 50130473
D9-V1-G-SGSOSRBZ2
Signaling column



Figure can vary

Contents

- Technical data
- Electrical connection

Technical data

| Basic data | |
|-------------------------------------|--------------------------|
| Series | D9 |
| Type of signaling | Optical and acoustic |
| Electrical data | |
| Life expectancy | > 100,000 h |
| Performance data | |
| Supply voltage U_B | 24 V, AC/DC, 10 % |
| Current consumption, max. | 194 mA |
| Connection | |
| Connection 1 | |
| Type of connection | Terminal |
| Mechanical data | |
| Design | Cubic |
| Dimension (W x H x L) | 90 mm x 194 mm x 45 mm |
| Housing material | Plastic |
| Housing color | White |
| Type of fastening, at system | Screw type / vertical |
| Type of illuminant | LED/24V |
| Lens modules | 3 pieces, ready-made |
| Signal image | Continuous light |
| Angle of radiation | 180° |
| Sequence of the modules (ascending) | Green, orange, red |
| Certifications | |
| Degree of protection | IP 65 |
| Certifications | c UL US |
| Acoustic data | |
| Tone type | Continuous or pulse tone |
| Audio frequency | Approx. 2500 Hz |
| Sound pressure | 70 ... 90 dB |
| Number of tones | 2 |
| Classification | |
| Customs tariff number | 85318070 |
| eCl@ss 8.0 | 27371230 |
| eCl@ss 9.0 | 27371230 |
| ETIM 5.0 | EC001042 |
| ETIM 6.0 | EC001042 |

Electrical connection

| Connection 1 | |
|--------------------|----------------|
| Type of connection | Terminal |
| Function | |
| Type of terminal | Screw terminal |