



Part no.: 50130479
P65-V1-B-DS-Y
Indicator



Figure can vary

Contents

- Technical data
- Electrical connection

Part no.: 50130479 – P65-V1-B-DS-Y – Indicator

Technical data

Basic data	
Type of signaling	Optical
Electrical data	
Life expectancy	> 100,000 h
Performance data	
Supply voltage U_B	24 V, AC/DC
Current consumption, max.	60 mA
Connection	
Connection 1	
Type of connection	Terminal
Mechanical data	
Design	Cylindrical
Dimension (\varnothing x L)	65 mm x 90 mm
Length in installed state	56 mm
Housing material	Plastic
Net weight	75 g
Housing color	Black
Type of fastening, at system	In bore holes with \varnothing 22.5 mm
Type of illuminant	LED/24V
Lens illumination	Full
Signal image	Continuous or flashing light
Lens color	Yellow
Angle of radiation	360°
Environmental data	
Ambient temperature, operation	-25 ... 60 °C
Certifications	
Degree of protection	IP 65
Certifications	c UL US
Classification	
Customs tariff number	85318070
eCl@ss 8.0	27371223
eCl@ss 9.0	27371223
ETIM 5.0	EC000272
ETIM 6.0	EC000272

Electrical connection

Connection 1	
Type of connection	Terminal

Part no.: 50130479 – P65-V1-B-DS-Y – Indicator

Connection 1	
Function	
Type of terminal	Removable screw terminals