



Figure can vary

Part no.: 50130514
P45-V1-B-DV
Indicator



Contents

- Technical data
- Electrical connection

Part no.: 50130514 – P45-V1-B-DV – Indicator

Technical data

Basic data

Type of signaling	Optical
-------------------	---------

Electrical data

Life expectancy	> 100,000 h
-----------------	-------------

Performance data

Supply voltage U_B	24 V, AC/DC
Current consumption, max.	39 mA

Connection

Connection 1

Type of connection	Terminal
--------------------	----------

Mechanical data

Design	Cylindrical
Dimension (\varnothing x L)	45 mm x 76 mm
Length in installed state	42 mm
Housing material	Plastic
Net weight	56 g
Housing color	Black
Type of fastening, at system	In bore holes with \varnothing 22.5 mm
Type of illuminant	LED/24V
Lens illumination	Half
Display of the lens colors	1 or 2 colors visible
Signal image	Continuous light
Lens color	Red, green
Angle of radiation	360°

Environmental data

Ambient temperature, operation	-25 ... 50 °C
--------------------------------	---------------

Certifications

Degree of protection	IP 65
Certifications	c UL US

Classification

Customs tariff number	85318070
eCl@ss 8.0	27371223
eCl@ss 9.0	27371223
ETIM 5.0	EC000272
ETIM 6.0	EC000272

Part no.: 50130514 – P45-V1-B-DV – Indicator

Electrical connection

Connection 1	
Type of connection	Terminal
Function	
Type of terminal	Removable screw terminals