



**Part no.: 50130520**  
**FBA-V1-Q94-R**  
**Indicator**



Figure can vary

## Contents

- Technical data
- Electrical connection
- Accessories

Part no.: 50130520 – FBA-V1-Q94-R – Indicator

## Technical data

### Basic data

Series	FBA
Type of signaling	Optical

### Optical data

Light intensity	30 cd
-----------------	-------

### Electrical data

Life expectancy	Approx. 50,000 h
-----------------	------------------

### Performance data

Supply voltage $U_B$	24 V, AC/DC, 10 %
Current consumption, max.	110 mA

### Connection

#### Connection 1

Type of connection	Terminal
--------------------	----------

### Mechanical data

Design	Cubic
Dimension (W x H x L)	94 mm x 94 mm x 97 mm
Housing material	Plastic
Net weight	230 g
Housing color	Red
Type of fastening, at system	Screw type
Type of illuminant	LED/24V
Signal image	Continuous or flashing light
Lens color	Red
Blink/flash frequency	1 Hz
Angle of radiation	180°

### Environmental data

Ambient temperature, operation	-30 ... 60 °C
--------------------------------	---------------

### Certifications

Degree of protection	IP 66
Certifications	c UL US
Resistance to shock	IK09 (EN 50295:98)

### Classification

Customs tariff number	85318070
eCl@ss 8.0	27371223
eCl@ss 9.0	27371223
ETIM 5.0	EC000272
ETIM 6.0	EC000272


Part no.: 50130520 – FBA-V1-Q94-R – Indicator

## Electrical connection

Connection 1	
Type of connection	Terminal
Function	
Type of terminal	Screw terminal

## Accessories

### Mounting technology - Other

	Part no.	Designation	Article	Description
	50130523	ACC-KT1	Mounting device	Functions: For connecting multi-tone sirens (EMS) and lights (FBA)