



**Part no.: 50130521**  
**FBA-V3-Q94-O**  
**Indicator**



Figure can vary

## Contents

- Technical data
- Electrical connection
- Accessories

Part no.: 50130521 – FBA-V3-Q94-O – Indicator

## Technical data

| <b>Basic data</b>              |                              |
|--------------------------------|------------------------------|
| Series                         | FBA                          |
| Type of signaling              | Optical                      |
| <b>Optical data</b>            |                              |
| Light intensity                | 30 cd                        |
| <b>Electrical data</b>         |                              |
| Life expectancy                | Approx. 50,000 h             |
| <b>Performance data</b>        |                              |
| Supply voltage $U_B$           | 230 V, AC/DC, 10 %           |
| Current consumption, max.      | 60 mA                        |
| <b>Connection</b>              |                              |
| <b>Connection 1</b>            |                              |
| Type of connection             | Terminal                     |
| <b>Mechanical data</b>         |                              |
| Design                         | Cubic                        |
| Dimension (W x H x L)          | 94 mm x 94 mm x 97 mm        |
| Housing material               | Plastic                      |
| Net weight                     | 230 g                        |
| Housing color                  | Red                          |
| Type of fastening, at system   | Screw type                   |
| Type of illuminant             | LED/24V                      |
| Signal image                   | Continuous or flashing light |
| Lens color                     | Orange                       |
| Blink/flash frequency          | 1 Hz                         |
| Angle of radiation             | 180°                         |
| <b>Environmental data</b>      |                              |
| Ambient temperature, operation | -30 ... 60 °C                |
| <b>Certifications</b>          |                              |
| Degree of protection           | IP 66                        |
| Certifications                 | c UL US                      |
| Resistance to shock            | IK09 (EN 50295:98)           |
| <b>Classification</b>          |                              |
| Customs tariff number          | 85318070                     |
| eCl@ss 8.0                     | 27371223                     |
| eCl@ss 9.0                     | 27371223                     |
| ETIM 5.0                       | EC000272                     |
| ETIM 6.0                       | EC000272                     |


Part no.: 50130521 – FBA-V3-Q94-O – Indicator

## Electrical connection

| Connection 1       |                |
|--------------------|----------------|
| Type of connection | Terminal       |
| Function           |                |
| Type of terminal   | Screw terminal |

## Accessories

### Mounting technology - Other

|   | Part no. | Designation | Article         | Description  |
|---|----------|-------------|-----------------|--|
|  | 50130523 | ACC-KT1     | Mounting device | Functions: For connecting multi-tone sirens (EMS) and lights (FBA) |