



Part no.: 50130522
FBA-V3-Q94-R
Indicator



Figure can vary

Contents

- Technical data
- Electrical connection
- Accessories

Part no.: 50130522 – FBA-V3-Q94-R – Indicator

Technical data

Basic data	
Series	FBA
Type of signaling	Optical
Optical data	
Light intensity	30 cd
Electrical data	
Life expectancy	Approx. 50,000 h
Performance data	
Supply voltage U_B	230 V, AC/DC, 10 %
Current consumption, max.	60 mA
Connection	
Connection 1	
Type of connection	Terminal
Mechanical data	
Design	Cubic
Dimension (W x H x L)	94 mm x 94 mm x 97 mm
Housing material	Plastic
Net weight	230 g
Housing color	Red
Type of fastening, at system	Screw type
Type of illuminant	LED/24V
Signal image	Continuous or flashing light
Lens color	Red
Blink/flash frequency	1 Hz
Angle of radiation	180°
Environmental data	
Ambient temperature, operation	-30 ... 60 °C
Certifications	
Degree of protection	IP 66
Certifications	c UL US
Resistance to shock	IK09 (EN 50295:98)
Classification	
Customs tariff number	85318070
eCl@ss 8.0	27371223
eCl@ss 9.0	27371223
ETIM 5.0	EC000272
ETIM 6.0	EC000272


Part no.: 50130522 – FBA-V3-Q94-R – Indicator

Electrical connection

Connection 1	
Type of connection	Terminal
Function	
Type of terminal	Screw terminal

Accessories

Mounting technology - Other

	Part no.	Designation	Article	Description
	50130523	ACC-KT1	Mounting device	Functions: For connecting multi-tone sirens (EMS) and lights (FBA)