



Part no.: 50130524
P65-V1-B-DS-O-BZ-103
Indicator light / acoustic indicator



Figure can vary

Contents

- Technical data
- Electrical connection

Part no.: 50130524 – P65-V1-B-DS-O-BZ-103 – Indicator light / acoustic

Technical data

Basic data

Type of signaling	Optical and acoustic
-------------------	----------------------

Electrical data

Life expectancy	> 100,000 h
-----------------	-------------

Performance data

Supply voltage U_B	24 V, AC/DC
Current consumption, max.	47 mA

Connection

Connection 1

Type of connection	Terminal
--------------------	----------

Mechanical data

Design	Cylindrical
Dimension (\varnothing x L)	65 mm x 93 mm
Length in installed state	58 mm
Housing material	Plastic
Net weight	110 g
Housing color	Black
Type of fastening, at system	In bore holes with \varnothing 22.5 mm
Type of illuminant	LED/24V
Lens illumination	Full
Signal image	Continuous or flashing light
Lens color	Orange
Angle of radiation	360°

Environmental data

Ambient temperature, operation	-25 ... 60 °C
--------------------------------	---------------

Certifications

Degree of protection	IP 65
Certifications	c UL US

Acoustic data

Tone type	Continuous or pulse tone
Audio frequency	Approx. 2800 Hz
Sound pressure	85 ... 103 dB
Number of tones	3

Classification

Customs tariff number	85318070
eCl@ss 8.0	27371290
eCl@ss 9.0	27371290
ETIM 5.0	EC000272
ETIM 6.0	EC000272

Electrical connection

Connection 1	
Type of connection	Terminal
Function	
Type of terminal	Removable screw terminals