



Part no.: 50130532
PBZ-V1-065
Acoustic indicator



Figure can vary

Contents

- Technical data
- Electrical connection

Part no.: 50130532 – PBZ-V1-065 – Acoustic indicator

Technical data

Basic data

Type of signaling	Acoustic
-------------------	----------

Electrical data

Performance data

Supply voltage U_B	12 ... 24 V, AC/DC
Current consumption, max.	46 mA

Connection

Connection 1

Type of connection	Terminal
--------------------	----------

Mechanical data

Design	Cylindrical
Dimension ($\varnothing \times L$)	30 mm x 59 mm
Length in installed state	12 mm
Housing material	Plastic
Net weight	30 g
Housing color	Black
Type of fastening, at system	In bore holes with \varnothing 22.5 mm

Environmental data

Ambient temperature, operation	-20 ... 60 °C
--------------------------------	---------------

Certifications

Degree of protection	IP 65
Certifications	c UL US

Acoustic data

Tone type	Continuous or pulse tone
Audio frequency	Approx. 3500 Hz
Sound pressure	65 dB
Number of tones	2

Classification

Customs tariff number	85318070
eCl@ss 8.0	27371214
eCl@ss 9.0	27371214
ETIM 5.0	EC001026
ETIM 6.0	EC001026

Electrical connection

Connection 1	
Type of connection	Terminal

Part no.: 50130532 – PBZ-V1-065 – Acoustic indicator

Connection 1	
Function	
Type of terminal	Removable screw terminals